

Technical Data Sheet



Burdett's Tooborac Toppings

Burdett's Tooborac Toppings is a suitable substitute for Granitic Sand / Gravel and has a tan - brown colour (refer image below).

Tooborac Toppings can be used for driveways and pathways; with suitable compaction, such as a vibrating plate it will provide a firm base.

Tooborac Toppings should ideally be placed at a depth of 50 – 75 mm over an equivalent thickness of solid base such as crushed rock.

It can be stabilised with cement at 3 – 5%.

Typical Properties:

- pH range: 4 – 7
- Low plasticity
- Silt content: Max. 6% by volume

Note: Colour and sizing may vary slightly as this is a natural product.



Head Office- Accounts:

Ph: 9789 8266 **Fax:** 8790 8713

Bulk Orders:

orders@burdetts.com.au

Ph: 5990 4700 (Option 1)

Sales Enquiries/Quotes:

phil@burdetts.com.au

Ph: 0477 661 179

IMPORTANT NOTICE: Above information is based on past test results and experience and is provided in good faith for assessment purposes only. This does not constitute a warranty made by any of the members of the Burdett Group. As Burdett's has no influence on the way in which these products are handled and used, we do not take any responsibility in this respect. You cannot rely solely upon this information to determine appropriate product use and must engage suitably qualified consultants to advise whether the product is fit for your end use.