

Technical Data Sheet



Burdett's Washed Sands

Burdett's washed sands are well-graded, low-silt products, washed to a high degree of cleanliness. Typical grading ranges (% retained) are below.

Sieve (mm)	White Washed Sand (%)	Coarse Washed Sand (%)
4.750	0 – 1	0 – 1
2.360	0 – 2	5 – 25
1.180	0 – 3	10 – 40
0.600	1 – 6	10 – 40
0.425	5 – 25	5 – 25
0.300	15 – 45	5 – 25
0.150	35 – 60	5 – 25
0.075	0 – 5	0 – 5
Pan	0 – 2	0 – 2

AFS	50 - 60	15 – 35
Eff. Size (d10)	0.12 – 0.22	0.25 – 0.45
C.o.U. (d60/d10)	1.5 – 2.5	3.2 – 4.2

Burdett's Washed Sands are available in bulk ex-bin or delivered from Quarry Road, Langwarrin or bagged at 615 McClelland Drive, Langwarrin. Tightly graded dried sands are available from third party providers.

Note: products may be manufactured to other specifications with prior arrangement – contact sales for further information.

IMPORTANT NOTICE: Above information is based on past test results and experience and is provided in good faith for assessment purposes only. This does not constitute a warranty made by any of the members of the Burdett Group. As Burdett's has no influence on the way in which these products are handled and used, we do not take any responsibility in this respect. You cannot rely solely upon this information to determine appropriate product use and must engage suitably qualified consultants to advise whether the product is fit for your end use.